

Order no.: 125121

# FlexxTower single-person scaffolding

Platform height [mm]

- 1100
- 2100
- 3100
- 4100



## Specification

Working height 3.1 m	Scaffolding length 3.12 m	Scaffolding width 2.55 m	Scaffolding height 2.3 m	Platform width 600 mm
Platform length 1.2 m	Load capacity 2 kN/m2	Transport dimensions 1400 x 800 x 600 mm, 69 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation possible & allowed
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation possible & allowed	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, indoor, lateral installation 0 kg	Ballasting of scaffolding, outdoor, central installation 0 kg
Ballasting of scaffolding, outdoor, lateral installation 20 kg	Business division MUNK Günzburger Steigtechnik	Platform height 1.1 m		

## Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights
- Can be quickly and safely assembled and disassembled by just one person (used by two) using the 3-T method from level to level

- Tool-free assembly thanks to push-fit connectors and quick-release connectors
- Easy to handle thanks to individual lightweight parts
- Space-saving transport and storage, as individual parts can be stacked compactly into each other and used as a trolley
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 125 mm swivel castors with centric load application and spindles
- Aluminium toe boards and powder-coated railing frames with integrated knee rail as a safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m<sup>2</sup>

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Flexible basis

- Castors Ø 125 mm with locking device
- Height adjustment for levelling

### Safe standing

- Folding triangular outrigger with swivel foot
- Also ideal for setting up against the wall or for transporting through narrow passages
- Simple to use



### Quickly and safely at a height

- Simple one-person assembly and disassembly from level to level (use by up to two people)
- Practical console for ladder simplifies transport and assembly of the individual components
- Users are now always in a safe place with the 3-T method

### Tool-free assembly and ease of transport

The new one-person FlexxTower scaffolding impresses with its robustness and quality, but can also be simply, quickly and safely assembled, thanks to the 3 T method (Through The Trapdoor). Users are always in a safe place, thanks to the pre-assembled double railings.

Quick-release fasteners and scaffolding claws provide added efficiency and safety during assembly, just like the practical suspended brackets for the transport of practical and lightweight aluminium components from level to level.

A trolley can also be constructed from a few components, again without the need for tools, in which the remaining scaffolding parts or even other materials can be quickly and ergonomically transported. And, thanks to its compact dimensions, the FlexxTower also fits through most doorways and can be transported in many commercial vehicles.


### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



### Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Expand your scaffolding with a safety railing (SG) and ensure reliable protection at work thanks to the system-integrated side protection! The retrofit reduces the risk of falling and enables the BG BAU work safety subsidy to be paid for up to 50% of the purchase costs (max. 100 euro per measure).

✓ Suitable for this product: Compatible SG safety railings offer effective side protection and are easy to retrofit.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: [www.bgbau.de/service/angebote/arbeitsschutzpraemie](http://www.bgbau.de/service/angebote/arbeitsschutzpraemie)

A brief overview of the subsidy and an overview of our eligible products can be found on our website at [Knowledge](#).

Corporate certifications

---

Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022

