

Order no.: 116128

# Evacuation stairs for rescue platform Premium



## Specification

Max. load capacity 150 kg	Material Aluminium	Weight 38 kg	Transport dimensions 1930 x 1170 x 180 mm, 38 kg	Business division MUNK Rettungstechnik
Order no. 116128				

## Facts

- Suitable for rescue platform Premium Art. 116050
- Design as flexible Vario staircase made of aluminium
- Tool-free adjustment and locking of the required inclination and height
- Les 4 montants sont équipés en série de rallonges de montants (compensation de hauteur de 300 mm max., blocage au pas de 30 mm)
- Steps made of anti-slip covering (R 13)
- Galvanised steel mounting parts

- Simple mounting on the platform pockets by means of locking bolts, possible on both sides
- Compulsory accessories for the evacuation staircase: Plug-in railing Art. 116129
- Perm. load: 150 kg

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022