



Order no.: 070632

FlexxGuard security door

Model versions

Specification

Total width 466.8 mm	Lockable Yes	Railing height 1.11 m	Design type Mobile	Material Aluminium coated
Colour RAL 1021	Transport dimensions (plus packaging) 850 x 650 x 60 mm, 7.7 kg	Business division MUNK Günzburger Steigtechnik	Order no. 070632	

Facts

- Easy assembly
- Safety door made of aluminium, coating in RAL 2004
- Safety door with integrated knee rail
- Shut-off rotatable (not coated)




Scope of supply

- Security door: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

With the mobile FlexxGuard modular safety railing system, you can easily secure hazardous areas on construction sites or in industrial plants and thus protect workers and visitors. The guardrails can be quickly and easily installed and secured on grating floors. Thanks to the flexible design, the FlexxGuard safety railing can be optimally adapted to requirements and thus guarantees the best possible protection.

A complete safety guardrail consists of at least:

- Telescopic guardrail: 1x or more
- Railing posts: 2x or more
- Safety gate: 1x or more (if access option required)

Advantages

- High level of safety
- Mobile application
- Quick and easy to assemble without tools
- Adaptable to various requirements
- Durable and low-maintenance

Assembly Variations

The FlexxGuard safety railing can be assembled in numerous variations. The components can be flexibly combined without tools, allowing hazards to be mitigated quickly and easily. Eye-catching design, thoughtful components, and high-quality materials ensure optimal protection.



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID: 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

