



Order no.: 058103

**Platform stairs, with  
single-sided access,  
with castors and  
handles, steel grating**



Number of steps

- 3
- 4
- 5
- 6
- 7
- 8

**Specification**

Working height <b>2.7 m</b>	Step design <b>Steps</b>	Number of steps/rungs <b>3 steps</b>	Platform included as step <b>Yes</b>	Step/Platform surface <b>Steel grating</b>
Non-slip class <b>R10</b>	Platform height <b>700 mm</b>	Height <b>1.72 m</b>	Platform length <b>800 mm</b>	Platform width <b>600 mm</b>
Step depth <b>200 mm</b>	Step/Rung distance <b>240 mm</b>	Inclination <b>60 °</b>	Depth of side-rails <b>57 mm</b>	Width of side-rails <b>24 mm</b>
Castor diameter <b>125 mm</b>	Base area length <b>1.24 m</b>	Base area width <b>770 mm</b>	Max. load capacity <b>150 kg</b>	Design type <b>Freestanding   Single-sided access   With castors</b>
Weight <b>37 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>058103</b>	Price <b>€ 1,232.00</b>	

**Facts**

- Aluminium platform stairs, single-sided
- Stable rectangular tube side-rails
- Steps with a depth of 200 mm

- Roomy platform (600 x 800 mm)
- with 3-sided 1,000 mm high railing with knee and toe boards
- Two Ø 125 mm lifting castors and handles for easily moving to new locations
- Easy to assemble (delivered unassembled)
- In accordance with DIN EN 131-7, handrails are optional for ascending platform ladders with an ascent angle  $\geq 60^\circ$
- Available in various step and platform designs
- Maximum load: 150 kg

### Scope of supply

- Platform stairs: 1 x
- Lifting castors: 2 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



## Certificates

---



5011053.24001 -  
Certificate Product  
Safety Type  
approved

Valid in



DIN EN 131-7:2013  
DIN EN 131-3:2018

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

