

Order no.: 115352

Telescopic ladder blue
DIN EN 1147



Specification

Rescue height 2.2 m	Intended use Rescue	Ladder length 3.5 m	Ladder length retracted 800 mm	Ladder length extended 3.5 m
Setting angle 70 °	Clear width between rungs 270 mm	Outer width 500 mm	Ladder feet Ladder shoe	Depth of side-rails 100 mm
Width of side-rails 80 mm	Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 11 rungs	Max. load capacity 216 kg
Persons max. 2	Material Aluminium	Rung covering blue	Weight 14 kg	Transport dimensions 940 x 560 x 130 mm, 14 kg
Business division MUNK Rettungstechnik	Order no. 115352			

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147

- Abrasion-resistant anodised octagonal tube side-rails
- With heat-insulating, non-slip plastic coating (DE and THW (Federal Agency for Technical Relief) designs)
- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- Permissible load: 250 kg / 2 people
- These products are covered by the statutory warranty

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548

