



Order no.: 120011

## Mobile container aluminium box

Type

Aluminium box

### Specification

Product type <b>Aluminium box</b>	Length <b>1.2 m</b>	Width <b>800 mm</b>	Height <b>1.19 m</b>	Height up to top edge of extension <b>821 mm</b>
Max. load capacity <b>500 kg</b>	Castor diameter <b>200 mm</b>	Braking system <b>Standard</b>	Filling height aluminium box <b>528 mm</b>	Number of levels <b>1</b>
Weight <b>82 kg</b>	Transport dimensions <b>1200 x 800 x 1185 mm, 102 kg</b>	Business division <b>MUNK Rettungstechnik</b>	Order no. <b>120011</b>	

### Facts

- Mobile container with "standard" undercarriage
- Aluminium box tight-welded in the lower area (filling height: 200 mm)
- Right side wall half-hinged on one side, flap made of galvanised steel
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro Light" undercarriage

- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip operation via continuous handle bar with non-slip and cold-insulating SoftGrip coating
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

### **Scope of supply**

- Mobile container: 1 x

### **Information on sustainability criteria**

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting

- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

