



Order no.: 019830

## Ladder holder powder-coated RAL 3000 with CL1 lock

Model versions

Red, CL1 lock Red, half cylinder

Red, Master Key

## Specification

Product type Zubehör	Length 260 mm	Width 131 mm	Height 150 mm	Adjustment range 95 mm
Material Stahl verzinkt   Stahl beschichtet	Transport dimensions (plus packaging) 160 x 155 x 155 mm, 1.2 kg	Predecessor product 019840	Business division MUNK Günzburger Steigtechnik	Order no. 019830

## Facts

- Prevents unauthorised removal – not a holder, but an anti-theft device
- Protects ladders from unauthorised removal – lockable wall-mounted security device
- Design in galvanised steel plate, then powder-coated in RAL 3000 Flame Red, for mounting on walls. Infinitely adjustable depth of 139 – 190 mm
- Infinitely adjustable depth from 139 -190 mm
- Dimensions approx. mm 150 x 131 x 165 – 260
- Suitable for stepladders and rung ladders

## Scope of supply

- Ladder safety device: 1 x

## Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Corporate certifications

---

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

