

Order no.: 012042

Pit ladder lower section



Number of steps

2

4

Specification

| | | | | |
|--|--|---|----------------------------------|------------------------------|
| Depth of excavation min. 1.3 m | Depth of excavation max. 1.6 m | Ladder length 800 mm | Number of steps/rungs 2 steps | Lower outer width 420 mm |
| Depth of side-rails 73 mm | Width of side-rails 25 mm | Step width 370 mm | Step depth 80 mm | Step/Rung distance 263 mm |
| Inclination 70 ° | Max. load capacity 150 kg | Type of non-slip protection clip-step R13 | Design type To lean against | Material Aluminium |
| Transport dimensions (plus packaging) 804 x 507 x 87 mm, 2.8 kg | Business division MUNK Günzburger Steigtechnik | Order no. 012042 | | |

Facts

- Aluminium ladder push-fit section
- Two different push-fit sections for flexible extension of the pit ladder
- 80 mm-deep steps with clip-step R13 slip-resistant step padding
- Easy and fast installation, thanks to push-fit connections with hook lock

- Tool-free conversion of pit ladder base plates with claws on push-fit section
- Lightweight individual components
- Space-saving transport and storage

Scope of supply

- Push-fit section: 1 x
- Assembly instructions and instructions for use: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)


- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:

www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website under [know-how](#).

Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

