

Order no.: 012049

Stepped pit ladder with folding exit rails



Specification

Depth of excavation min. 800 mm	Depth of excavation max. 1.05 m	Ladder length 2.25 m	Number of steps/rungs 4	Platform included as step Ja
Lower outer width 490 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm	Step width 440 mm	Step depth 80 mm
Step/Rung distance 263 mm	Platform length 240 mm	Platform width 550 mm	Inclination 70 °	Max. load capacity 150 kg
Type of non-slip protection clip-step R13	Design type Zum Anlehnen	Handrails included Ja	Material Aluminium	Transport dimensions (plus packaging) 1260 x 588 x 195 mm, 10.2 kg
Business division MUNK Günzburger Steigtechnik	Order no. 012049			

Facts

- Aluminium step straight ladder
- 80 mm-deep steps with clip-step R13 slip-resistant step padding

- 4-fold edged step-to-side-rail connection
- Folding 1.0 m exit rails for safe access
- Extra-wide, height-adjustable platform (550 x 240 mm), consisting of slip-resistant perforated aluminium cover R13 for safe entry/exit, and to lock the ladder at the edge of the pit
- Base plates with claws for secure footing at the correct working angle
- Flexible means of extension thanks to optional push-fit sections
- Step spacing: 263 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Ideal and flexible for use in raised floors

Scope of supply

- Ladder: 1 x
- Swivel foot, claw: 2 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- **Recyclability:** Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- **Socially acceptable working conditions in production:** fair wages, gender equality
- **Economical and recyclable packaging:** no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- **No health hazards for the users**

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories


- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Corporate certifications

Standards for quality and sustainability

