

Order no.: 077435

Sprouted double-barred mast ladder

type

Lower part

Plug-in part 1

Plug-in part 2



Specification

Ladder length 1.95 m	Number of steps/rungs 7 rungs	Outer width 645 mm	Depth of side-rails 58 mm	Max. load capacity 150 kg
Business division MUNK Günzburger Steigtechnik	Order no. 077435	Length 2.05 m		

Facts

- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 470 mm
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life
(including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Corporate certifications

Standards for quality and sustainability

