



Order no.: 052090

Platform ladder for sanitary installations



Number of steps

3

4

5

Specification

Working height 2.69 m	Step design Stufen	Number of steps/rungs 3 steps	Platform included as step Ja	Platform height 687 mm
Step depth 80 mm	Step/Rung distance 235 mm	Height 1.44 m	Base spread 848 mm	Inclination 70 °
Lower outer width 574 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Design type Freistehend Einseitig begehbar	Transport dimensions (plus packaging) 1437 x 574 x 164 mm, 8.9 kg	Business division MUNK Günzburger Steigtechnik	Order no. 052090	

Facts

- Platform ladder made of aluminium
- Works directly above the toilet, perfect for narrow cubicles, limited space and for ceiling and wall work
- Full work surface without space issues, fits perfectly in sanitary cubicles and enables ceiling and wall work

Description

The platform ladder for sanitary cubicles has been specially developed for use in confined spaces. Its sophisticated design allows the work platform to be positioned directly above a toilet without causing space problems. This makes it the ideal solution for maintenance, cleaning or installation work in narrow sanitary cubicles or changing rooms. The spacious, non-slip platform provides a secure

- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Large, trapeze-shaped platform (400 / 340 x 425 mm)
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- Two handrails for safe ascent and descent (enclosed separately)
- 'safe-cap' ladder joint
- Practical storage tray (350 x 200 mm)
- Rigid connection through metal struts detachable on both sides
- Spreader lock with two high-strength polyester straps
- Two castors, Ø 125 mm, for easy movement from place to place
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

footing and sufficient freedom of movement to carry out ceiling and wall work efficiently.

Thanks to the integrated transport rollers, the ladder can be easily moved, which is particularly advantageous when working in different locations in sanitary facilities. When folded, it can be stored in a space-saving manner and fits through any standard door. The side handrails provide a stable hold when ascending and descending and increase work safety – even in wet floor conditions.

Made of lightweight, robust aluminium, the platform ladder is ideal for daily use in demanding work environments. It is specifically aimed at professional users in facility management, building cleaning, the skilled trades and the sanitary and building services industry. Its combination of compact design, high functionality and practical features makes it an indispensable tool wherever space is limited but full performance is required.

Scope of supply

- Ladder: 1 x
- Handrail (enclosed separately): 2 x
- Lifting castors: 2 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct

- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

