



Order no.: 930207

# Corner bracket 30x30 mm

Туре



# Specification

| Connection type  | Material    | Weight/piece | Groove size | Dimension A |
|------------------|-------------|--------------|-------------|-------------|
| Angle connection | Die-cast    | 23 g         | 6 mm        | 30 mm       |
| Dimension B      | Dimension C | Dimension D  | Order no.   |             |
| 30 mm            | 30 mm       | 5 mm         | 930207      |             |

## Facts

- Profile angle for profile 30
- For joining profiles to each other
- Particularly suitable for retrofitting profiles

## Description

Secure 90° connections for modular construction kits – optionally for groove 6 in 30 mm profiles or groove 8 in 40 mm profiles.

Key advantages

- Universally applicable: Suitable for all MUNK construction profiles 30 × 30 mm (groove 6) or 40 × 40 mm (groove 8) – ideal for right-angled frames, racks and protective enclosures.
- Easy to retrofit: Can be swivelled into open grooves; perfect for extensions without dismantling entire assemblies.



- Robust & durable: Die-cast body with 5 mm wall thickness for high clamping forces and permanent angle stability.
- Clean appearance: Internal screws conceal fastening points and ensure smooth outer surfaces.

#### Typical applications

- Machine frames: Reinforcement of 30 or 40 mm profiles without welding.
- Protective and test enclosures: Quick assembly of stable 90° frames with glass or mesh panels.
- Assembly tables and workstations: Retrofitting of shelves, guide plates or swivel arms.
- Transport racks: Torsion-resistant corner connections for tow tractors and load carriers.

#### Assembly instructions

Insert or swing in the groove nut (not included), attach the corner bracket, tighten the screw (not included) with an Allen key – done. The connection remains detachable and can be moved or extended at any time.

## Scope of supply

Corner bracket: 1 x

## Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct



- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures





# Corporate certifications

Standards for quality and sustainability





