



Order no.: 040352

## Level access ladder



Number of steps

12

14

16

## Specification

|   |  |   |  |                                     |
|---|--|---|--|-------------------------------------|
| Step design<br><b>Steps</b>                         | Number of steps/rungs<br><b>12 steps</b> | Step width<br><b>371 mm</b>                                 | Step depth<br><b>80 mm</b>                               | Step/Rung distance<br><b>235 mm</b> |
| Type of non-slip protection<br><b>clip-step R13</b> | Ladder length<br><b>3.14 m</b>           | Inclination<br><b>70 °</b>                                  | Base area<br><b>1.22 m</b>                               | Outer width<br><b>470 mm</b>        |
| Stabiliser width<br><b>930 mm</b>                   | Depth of side-rails<br><b>73 mm</b>      | Width of side-rails<br><b>25 mm</b>                         | Max. load capacity<br><b>150 kg</b>                      | Design type<br><b>To hang up</b>    |
| Handrail length<br><b>1.3 m</b>                     | Weight<br><b>16.5 kg</b>                 | Transport dimensions<br><b>3000 x 420 x 300 mm, 16.5 kg</b> | Business division<br><b>MUNK Günzburger Steigtechnik</b> | Order no.<br><b>040352</b>          |
| Price<br><b>€ 1,197.00</b>                          |  |   |  |                                     |

## Facts

- Aluminium step straight ladder
- Stable rectangular tube side-rails

- 80 mm-deep steps with clip-step R13 slip-resistant step padding
- 4-fold edged step-to-side-rail connection
- Standard stabiliser 930 mm with non-slip ladder shoes
- Two rigid exit side-rails that can be attached without tools (enclosed loose)
- Two pre-assembled handrails for safe ascent and descent
- Two pre-assembled ladder head protection beams
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Handrail (mounted): 2 x
- Exit rail: 2 x
- Ladder head protection: 2 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---




## Added value

---

### clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



### Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

