



Order no.: 116125

# **Equipment maintenance ladder**

# **Specification**

Working height <b>4.7 m</b>	Number of steps/rungs 2x 6 rungs	Step width 300 mm	Step/Rung height <b>30 mm</b>	Step depth 30 mm
Step/Rung distance 280 mm	Type of non-slip protection Aluminium corrugated	Length of ladder sections 1.7 m	Ladder length as straight ladder <b>3.6 m</b>	Ladder length as double-sided ladder <b>1.85 m</b>
Base spread as double ladder 1.21 m	Inclination 72.5 °	Stabiliser width <b>646 mm</b>	Depth of side-rails <b>58 mm</b>	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding   Double-sided access	Weight <b>9 kg</b>	Transport dimensions <b>x x mm, 9 kg</b>	Business division MUNK Rettungstechnik
Order no. <b>116125</b>				

## **Facts**

- Aluminium folding rung ladder
- Stable rectangular tube side-rails



- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step and straight ladder
- Optimum operational safety due to six automatically locking steel hinges
- nivello® ladder shoes with patented 2-axis inclination technology
- Stabiliser for extra safe footing and ascent (enclosed separately)

Rung distance: 280 mm

Ladder width: 350 mm

Maximum load: 150 kg

- Side-rail and stabiliser powder-coated in red
- Foil lettering on one side "Die Gerätewartleiter"

#### Scope of supply

Ladder: 1 x

Instructions for use and operation: 1 x

## Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

#### More product pictures





# **Corporate certifications**

on sustainability criteria









