



Order no.: 027991

Protective assembly railing telescopic

Specification

Length 3.08 m	Height 1.41 m	Suitable for Mobile scaffolding	Transport dimensions 1580 x 220 x 160 mm, 7.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 027991				

Facts

- Additional folding frame for setup and dismantling of mobile scaffolding to minimise the risk of falling
- Easy to assemble from the ground or from the platform already secured by struts by hooking the claws into the scaffolding frame
- Secured with hooks
- Simple to install without the need for tools
- Telescopic, therefore suitable for platform lengths 1.80–3.0 m



Note: According to DIN EN 1004, the erection, and dismantling of rolling scaffolds without without personal protective equipment against must be possible. By using two safety railings, this requirement can be requirement can be fulfilled.

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
 small amounts of plastic
- No health hazards for the users



More product pictures





Corporate certifications

on sustainability criteria







