

Order no.: 027991

## Protective assembly railing telescopic



### Specification

Length 3.08 m	Height 1.41 m	Suitable for Rollgerüste	Transport dimensions (plus packaging) 1580 x 220 x 160 mm, 7.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 027991				

### Facts

- Additional folding frame for setup and dismantling of mobile scaffolding to minimise the risk of falling
- Easy to assemble from the ground or from the platform already secured by struts by hooking the claws into the scaffolding frame
- Secured with hooks
- Simple to install without the need for tools
- Telescopic, therefore suitable for platform lengths 1.80–3.0 m

- Note: According to DIN EN 1004, the erection, and dismantling of rolling scaffolds without personal protective equipment against must be possible. By using two safety railings, this requirement can be fulfilled.

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Corporate certifications

---

### Standards for quality and sustainability

