



Order no.: 019239

Push-fit exit side-rail

Type

straight

inclined

Specification

Product type	Length	Width	Diameter	Material
Accessories	1.41 m	118 mm	35 mm	Aluminium
Transport dimensions 1410 x 50 x 35 mm, 1.47 kg	Business division MUNK Günzburger Steigtechnik	Order no. 019239		

Facts

- Side-rail made of aluminium tube Ø 35 mm
- For vertical extension of the ladder for a safe bridging step
- Suitable for all ladders with rung spacing of 280 mm and step spacing of 235 mm or 263 mm
- For tool-free installation via ergonomic star handle
- Fastening via clamping mechanism in the uppermost rung/step holes
- Available as straight or inclined variant
- Can be mounted either on the right or left side of the ladder



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

Standards for quality and sustainability









