

Order no.: 019294

Tension and compression resistant connecting strut



Specification

Product type Accessories	Length 490 mm	Width 99.5 mm	Height 60 mm	Suitable for ladder type Double-sided ladders
Material Aluminium	Transport dimensions (plus packaging) 490 x 99.5 x 60 mm, 0.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 019294	

Facts

- High-strength, tensile and pressure-resistant aluminium securing mechanism with joint for stepladders up to ladder size 2 x 10
- For maximum safety at work, correct ladder positioning is ensured by pressure-resistant bracing, optimum stability and prevention of the impermissible slippage of the ladder
- Simple to fix in place by means of a clamping mechanism in the rung/step edge opening
- For retrofitting

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability

