

Order no.: 019294

Tension and compression resistant connecting strut





Specification

Product type	Length	Width	Height	Suitable for ladder type
Accessories	490 mm	99.5 mm	60 mm	Double-sided ladders
Material Aluminium	Transport dimensions 490 x 99.5 x 60 mm, 0.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 019294	

Facts

- High-strength, tensile and pressure-resistant aluminium securing mechanism with joint for stepladders up to ladder size 2 x 10
- For maximum safety at work, correct ladder positioning is ensured by pressure-resistant bracing, optimum stability and prevention of the impermissible slippage of the ladder
- Simple to fix in place by means of a clamping mechanism in the rung/step edge opening
- For retrofitting

Information on sustainability criteria



Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures











Corporate certifications

on sustainability criteria







