

Order no.: 062180

Mounting kit ballast for parapet crossings



Specification

Length 450 mm	Height 149 mm	Material Plastic Aluminium	Weight 57.12 kg	Transport dimensions 450 x 450 x 149 mm, 57.12 kg
Business division MUNK Günzburger Steigtechnik	Order no. 062180	Price € 398.00		

Facts

- Welded aluminium frames with stackable plastic weights
- For mounting on roof parapet bridges and support on roof surfaces
- 1 set = 2 items
- Slopes in roofs (up to 14° / 25%) can be balanced out
- Mountable in 2 directions
- Incl. 4 x 12.5 kg ballast weights
- Incl. building protection mat to protect roof surfaces

Scope of supply

- Frame for attic ballast: 2 x
- Installation material: 2 x
- Building protection mat: 2 x
- Ballast weight: 4 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All [fixed ladders / vertical ladders](#) at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#).
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#)

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

