

Gebrauchs- und Betriebsanweisung beachten!
Steigleiter gemäß den gesetzlichen Vorgaben regelmäßig prüfen.

Steigleiter mit Rückenschutz

Steigleiter mit Rückenschutz

Steigleiter mit Buckenschutz

Steigleiter an baulichen Anlagen
DN EN 150 14122-42016-10

Steigleiter mit Steigschutz:

Benutzung der persönlichen Schutzausrüstung ist vorgeschrieben
Steigleiter nur mit geeignetem Auffanggurt und zugehörigem
Auffanggerät beeutzen.

Auffanggerät Steigschutzeinrichtung GÜFA nach EN 353-1
Persönliche Schutzausrüstung gegen Absturz Mittaufende Auffanggerät einschließeich fester Führung

Persönliche Schutzausrüstung gegen Absturz Mittaufende Auffanggerät einschließeich fester Führung

Persönliche Schutzausrüstung muss gemäß den gesetzlichen
Vorgaben, mindestens einmal jährlich überprüft werden.

Montijert amc 1 2 3 4 5 6 7 8 9 10 11 12 21 122 23 124 125

Order no.: 019107

Identification sticker for fall protection device

Specification

Outer width 170 mm	Height 95 mm	Material Plastics	Transport dimensions 20 x 20 x 1 mm, 1 kg	Business division MUNK Günzburger Steigtechnik
Order no. 019107				

Facts

- Easy-to-understand identification for increased safety
- Supports compliance with safety regulations and standards
- For attachment at every entry and exit point for vertical ladders in accordance with DIN 18799-1 and DIN EN ISO 14122-4 and for vertical ladders with fall protection

Scope of supply

■ Plate: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001



Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight <u>emergency ladder</u> <u>systems (emergency ladders)</u>
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



Corporate certifications

on sustainability criteria









