



Order no.: 040684

# 2-section step ropeextension ladder with nivello® stabiliser



Number of steps



# Specification

Working height 7 m	Step design Steps	Number of steps/rungs 2x 12 steps	Step depth 80 mm	Step/Rung distance 263 mm
Retracted length 3.62 m	Extended length 6.42 m	Length of ladder sections 3.62 m	Inclination 70 °	Outer width 420 mm
Stabiliser width 1.2 m	Depth of side-rails 85 mm	Width of side-rails 25 mm	Design type To lean against   2- part	Transport dimensions 3500 x 400 x 200 mm, 22.3 kg
Business division MUNK Günzburger Steigtechnik	Order no. 040684			

# **Facts**

- Step rope-extension ladder, aluminium
- Complies with standard DIN EN 131-2 and TRBS 2121 Part 2
- Stable rectangular tube side-rails
- 4-fold edged step-to-side-rail connection
- Grooved steps with a depth of 80 mm



- Galvanised steel fittings
- Convenient height adjustment from step to step, thanks to rope pulley with plastic rope arranged on the left side
- Upper ladder with wall wheels, without crosstube, therefore suitable for access
- Lower ladder with nivello® stabiliser for extra stability and safe ascent (enclosed separately)
- Self-locking double locking hook
- 'Roll-bar' retrofit kit for enhanced ergonomics, available as an accessory
- Step spacing: 263 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- Attention! All accessory attachments such as handrails or exit rails can only be fitted to the ladder when the ladder is in the extended position and is no longer extended or retracted.
- Mounting of hooks not possible

#### Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

Instructions for use and operation: 1 x

#### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct



- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures









#### Added value

#### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part





#### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



The movable ladder shoe sets new standards in stability

Learn more





# Corporate certifications

## Standards for quality and sustainability









