



Order no.: 033106

Rung straight ladder, wood without stabiliser



Number of rungs

6 8 10 12 14

Specification

| | | | | |
|------------------------------|--------------------------------|---|--|------------------------------|
| Working height 3 m | Step design Rungs | Number of steps/rungs 6 rungs | Step/Rung height 40 mm | Step depth 21 mm |
| Step/Rung distance 280 mm | Ladder length 1.92 m | Outer width 420 mm | Depth of side-rails 61 mm | Width of side-rails 27 mm |
| Max. load capacity 150 kg | Design type To lean against | Transport dimensions (plus packaging) 1920 x 420 x 60 mm, 4 kg | Business division MUNK Günzburger Steigtechnik | Order no. 033106 |

Facts

- Rung straight ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg

- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths



Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Certificates



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID: 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

