



Order no.: 033120

Roof ladder wood



Number of rungs

- 10
- 12
- 14
- 16
- 18

Specification

Ladder length 2.8 m	Number of steps/rungs 10 rungs	Step/Rung distance 280 mm	Outer width 350 mm	Depth of side-rails 29 mm
Design type To hang up	Transport dimensions 2800 x 350 x 65 mm, 6.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033120	

Facts

- For installation on roof pitches from 22.5° to 75° and for load distribution during roofing work according to standard DIN 4567-4
- Caroline pine or finger-jointed pine side-rails with bevelled ends for easy handling
- Side-rails with strong, upwardly curved rungs; waterproof glued, weatherproof glazed and screwed 4 times per rung
- Ladder width: 350 mm
- Rung distance: 280 mm

- Note: In accordance with German Social Accident Insurance (DGUV) information sheet 201-054, roof ladders must be suspended in safety roof hooks as per DIN EN 517 (not in the top rung). Use as a straight ladder is not permitted

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life
(including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

