



Order no.: 033306

Multi-purpose ladder, 3part, with nivello® crossbar and wall rollers



Number of rungs

| | 3x6 | 3x8 | 3x10 | 3x12 | 3x14 |
|---|-----|-----|------|------|------|
| 1 | | | | | |

Specification

| Working height 5.2 m | Step design Rungs | Number of steps/rungs 3x 6 rungs | Step/Rung height 30 mm | Step depth 30 mm |
|------------------------------|--|---|---|--|
| Step/Rung distance 280 mm | Ladder length, two-part, straight 3.07 m | Ladder length, three- part, straight 4.19 m | Ladder length, 2-part, double-sided with attachable section 2.97 m | Base spread as double ladder 1.3 m |
| Inclination 70 ° | Retracted length 1.94 m | Length of ladder sections 1.94 m | Outer width 490 mm | Stabiliser width 930 mm |
| Depth of side-rails 73 mm | Width of side-rails 25 mm | Max. load capacity 150 kg | Transport dimensions 1922 x 505 x 200 mm, 14.5 kg | Business division MUNK Günzburger Steigtechnik |
| Order no. 033306 | | | | |

Facts

- Multi-purpose rung ladder made from aluminium
- Stable rectangular tube side-rails



- Rectangular rungs grooved on both sides, 30 x
 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step ladder, straight ladder and push-up extension ladder
- Suitable for stairs with ladder length up to 3.0 m
- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder with wall wheels
- nivello® ladder shoes and nivello® stabiliser (enclosed separately)
- Spreader lock with two high-strength polyester straps and detachable metal strut
- Rung distance: 280 mm
- Ladder width: 490 mm (without stabiliser)
- Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification



- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



The movable ladder shoe sets new standards in stability

Learn more



Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part





roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





Corporate certifications

Standards for quality and sustainability









