

ł

ß



Order no.: 050203

Platform stairs, with doublesided access, with springloaded castors, grooved aluminium

Number of steps



Specification

Working height	Step design	Number of steps/rungs	Platform included as step	Step/Platform surface
2.7 m	Steps	2x 3 steps	Yes	Aluminium corrugated
Non-slip class	Platform height	Height	Platform length	Platform width
R9	720 mm	1.72 m	800 mm	600 mm
Step depth	Step/Rung distance	Inclination	Depth of side-rails	Width of side-rails
200 mm	240 mm	60°	57 mm	24 mm
Castor diameter 125 mm	Base area length 1.51 m	Base area width 770 mm	Max. load capacity 150 kg	Design type Freestanding Double- sided access With castors
Transport dimensions 1516 x 778 x 718 mm, 30 kg	Business division MUNK Günzburger Steigtechnik	Order no. 050203		

Facts

- Aluminium platform stairs double-sided
- Stable rectangular tube side-rails
- Steps with a depth of 200 mm
- Roomy platform (600 x 800 mm)
- Railing on both sides and knee and toe board for safe stance (height: 1,000 mm)
- Four Ø 125 mm self-locking swivel castors, 2 with locking device
- Easy to assemble (delivered unassembled)



- In accordance with DIN EN 131-7, handrails are optional for ascending platform ladders with an ascent angle ≥ 60°
- Available in various step and platform designs
- Maximum load: 150 kg

Scope of supply

- Platform stairs: 1 x
- Swivel castor: 4 x

Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Certificates



5011053.24001 -Certificate Product Safety Type approved

DIN EN 131-7:2013 DIN EN 131-3:2018 Industrial grade

Stable and robust for tough everyday working life (including 4way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories





Corporate certifications

on sustainability criteria

