



Order no.: 065008

## Entry aid, double side-rails, galvanised steel

for ladder width [mm]

340

440

### Specification

Outer width <b>340 mm</b>	Suitable for <b>Shaft ladders</b>	Weight <b>5.5 kg</b>	Transport dimensions <b>1570 x 335 x 90 mm, 5.5 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Order no. <b>065008</b>	Price <b>€ 197.00</b>			

### Facts

- not for GRP shaft ladders
- Made of pickled and passivated V4A (1.4571) stainless steel or galvanised steel
- Can be lowered, complete with fixtures for ladder side-rail, 50 x 20 mm
- For ladder widths 340 and 440 mm

### Scope of supply

- Entry aid: 1 x
- Assembly instructions: 1 x

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

