

Order no.: 115004

Scaling ladder connecting section DIN EN 1147



Specification

Outer width 466 mm	Ladder feet Leiterschuh	Depth of side-rails 74 mm	Width of side-rails 35 mm	Max. load capacity 300 kg
Persons max. 2	Material Aluminium	Transport dimensions (plus packaging) 494 x 566 x 192 mm, 5.2 kg	Business division MUNK Rettungstechnik	Order no. 115004

Facts

- Scaling ladder connecting section made of aluminium
- Suitable for scaling ladders made of aluminium and wood
- For creating a double-sided ladder or a provisional hose conveyance
- Secure push-fit connections with spring-loaded locking pin
- Surface of the platform made of aluminium chequered plate, approx. 310 x 260 mm
- With integrated eye for attaching a snap hook or shackle

- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Permissible load: 300 kg

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

