



Order no.: 115020

Rescue and working platform with folding frame DIN 14830

Specification

Platform height max. 1.87 m	Platform length 1.8 m	Platform width 800 mm	Railing height 970 mm	Surface Natural aluminium grating
Non-slip class R12	Outer width 800 mm	Clear width 1.8 m	Compensation of floor unevenness 270 mm	Max. load capacity 500 kg
Material Aluminium	Weight 59 kg	Transport dimensions 1800 x 940 x 450 mm, 59 kg	Business division MUNK Rettungstechnik	Order no. 115020

Facts

- Rescue platform compliant with DIN 14830
- For rescuing injured persons from trucks, buses and trains
- Can also be used as a working platform
- Sturdy aluminium design with non-slip grating (R 12)
- Platform height can be adjusted in stages
- Folding frame unit

- Four spindle feet for infinitely variable levelling by up to approx. 270 mm
- Platform size: 1,800 x 800 mm
- Permissible load: 500 kg

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

