



Order no.: 115095

## Scaffolding bracket, multi-function ladder, DIN EN 1147

### Specification

Max. load capacity <b>216 kg</b>	Persons max. <b>2</b>	Material <b>Galvanised steel</b>	Weight <b>2.5 kg</b>	Transport dimensions <b>895 x 285 x 68 mm, 2.5 kg</b>
Business division <b>MUNK Rettungstechnik</b>	Order no. <b>115095</b>			

### Facts

- Aluminium scaffolding bracket
- Suitable for multi-function ladder 115093
- (2x required)
- For setting up a ladder platform with working platform 115099 (not included in scope of delivery)
- Scope of delivery: 2x

### Information on sustainability criteria

- Corporate certification: ISO 9001

- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

