

Order no.: 115096

## Connecting section, multi- function ladder DIN EN 1147



### Specification

Clear width as double ladder 2.67 m	Clear height of the attachment point 3.56 m	Outer width 570 mm	Ladder feet Ladder shoe	Max. load capacity 250 kg
Material Aluminium	Rung covering Standard (red)	Weight 14 kg	Transport dimensions 885 x 570 x 330 mm, 14 kg	Business division MUNK Rettungstechnik
Order no. 115096				

### Facts

- Connecting section made of aluminium
- Suitable for multi-function ladder 115093 (2x required)
- For creating a double-sided ladder, bridging step, tripod or hose conveyance
- Secure push-fit connections with spring-loaded locking pin
- With integrated eye for attaching a snap hook or shackle

- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Permissible load: 300 kg

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

