



Order no.: 120006

## Mobile container breathing apparatus

### Type

**Breathing apparatus**

Breathing apparatus and spare bottles

Breathing apparatus boxes

Breathing apparatus boxes and spare bottles

## Specification

Product type Breathing apparatus	Length 1.2 m	Width 800 mm	Height 1.19 m	Height up to top edge of extension 1.19 m
Max. load capacity 500 kg	Castor diameter 200 mm	Braking system Standard	Number of levels 3	Number of breathing apparatuses 6
Number of breathing apparatus cylinders 0	Transport dimensions (plus packaging) 1200 x 800 x 1185 mm, 142 kg	Business division MUNK Rettungstechnik	Order no. 120006	

## Facts

- Mobile container with "standard" undercarriage
- For the safe and protected transport of six breathing apparatuses (single canister) and six respirator masks with filters and regulators
- Closed structure made of 12 mm wooden platform boards
- Division into three storage levels with closing flaps
- Including three storage trays made of aluminium with handle (L x W x H: (673 x 222 x 230 mm))

- Compartment for breathing apparatus (L x W x H 730 x 410 x 270 mm)
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip operation via continuous handle bar with non-slip and cold-insulating SoftGrip coating
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake
- DEKRA certificate: Load securing in connection with load securing system

### Scope of supply

- Mobile container: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS

- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures


---



## Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

## Certificates



## Corporate certifications

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID: 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

