



Order no.: 033510

## Double-sided rung ladder suitable for stairs



Number of rungs

2x5

2x6

2x7

2x8

### Specification

Working height <b>3.6 m</b>	Step design <b>Rungs</b>	Number of steps/rungs <b>2x 5 rungs</b>	Step/Rung height <b>30 mm</b>	Step depth <b>30 mm</b>
Step/Rung distance <b>280 mm</b>	Type of non-slip protection <b>Aluminium corrugated</b>	Height <b>1.47 m</b>	Ladder length <b>1.5 m</b>	Base spread <b>1.08 m</b>
Base spread max. extended <b>1.56 m</b>	Inclination <b>70 °</b>	Lower outer width, ascent unit extended <b>640 mm</b>	Lower outer width, ladder retracted <b>600 mm</b>	Lower outer width, support part extended <b>700 mm</b>
Max. adjustment range on the ascent unit <b>400 mm</b>	Max. adjustment range on the support part <b>1 m</b>	Depth of side-rails <b>58 mm</b>	Width of side-rails <b>25 mm</b>	Max. load capacity <b>150 kg</b>
Design type <b>Freestanding   Double-sided access   Suitable for stairs</b>	Weight <b>11 kg</b>	Transport dimensions <b>1535 x 590 x 225 mm, 11 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>033510</b>
Price <b>€ 668.00</b>				

### Facts

- Double-sided rung ladder made of aluminium

- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- Solid, galvanised steel hinges with screw attachment
- Plastic end caps on upper side-rail end
- Spreader lock with two high-strength polyester straps
- Transport securing straps
- Rung distance: 280 mm
- Four bar extensions with solid sliding guide and ergonomic star handle
- Adjustment range on the ascent section: max. 400 mm
- Adjustment range on the support section: max. 1,000 mm
- Maximum load: 150 kg

### **Scope of supply**

- Ladder: 1 x

### **Information on sustainability criteria**

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size

- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories




The movable ladder shoe sets new standards in stability

[Learn more](#)



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Certificates

---



17KFP1657-02 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-  
3:2007  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK  
EK5-AK1 17-  
02:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

