

Order no.: 116050

## Rescue and working platform Premium



### Specification

Platform height min. <b>880 mm</b>	Platform height max. <b>1.68 m</b>	Platform length <b>1.72 m</b>	Platform width <b>830 mm</b>	Railing height <b>1 m</b>
Surface <b>Aluminium heavily corrugated</b>	Non-slip class <b>R13</b>	Outer width <b>929 mm</b>	Clear width <b>2.29 m</b>	Compensation of floor unevenness <b>250 mm</b>
Step/Rung height <b>28 mm</b>	Step depth <b>29 mm</b>	Number of steps/rungs <b>2x 3 rungs</b>	Max. load capacity <b>500 kg</b>	Material <b>Aluminium</b>
Weight <b>49 kg</b>	Transport dimensions <b>1800 x 1045 x 277 mm, 49 kg</b>	Business division <b>MUNK Rettungstechnik</b>	Order no. <b>116050</b>	

### Facts

- Rescue platform compliant with DIN 14830
- For rescuing injured persons from trucks, buses and trains
- Can also be used as a working platform
- Sturdy structure made of aluminium
- Platform with non-slip coating (R 13)

- Non-slip and ribbed rungs
- Adjustable platform height using ergonomically shaped handles
- Sturdy locking bolts for secure locking in a grid of 265 mm
- Folding access ladders on both sides with self-locking steel hinges
- All four side-rails with side-rail extensions as standard (height compensation of max. 250 mm, locking in 30 mm increments)
- Folding railing can be used on the left or right
- Long luminescent markings for better visibility in the dark
- Platform size: 1,720 x 830 mm
- Permissible load: 500 kg

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Corporate certifications

---

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548

