



Order no.: 116102

Scaling ladder upper section ÖNORM F 4047

Specification

Intended use Rescue	Ladder length 2.7 m	Setting angle 70 °	Clear width between rungs 245 mm	Outer width 483 mm
Ladder feet Ladder shoe	Depth of side-rails 74 mm	Width of side-rails 35 mm	Step/Rung height 28 mm	Step depth 29 mm
Number of steps/rungs 7 rungs	Step/Rung distance 273 mm	Max. load capacity 216 kg	Persons max. 2	Material Aluminium
Weight 9.4 kg	Transport dimensions 2660 x 577 x 85 mm, 6 kg	Business division MUNK Rettungstechnik	Order no. 116102	

Facts

- Rescue ladder, made of aluminium, compliant with ÖNORM F4047
- Secure push-fit connections with spring-loaded locking pin
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance

- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Upper ladder with box profile rung made of aluminium chequered plate
- Permissible load: 2 persons

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

