

Order no.: 116103

Scaling ladder push-fit section ÖNORM F 4047



Specification

Ladder length 750 mm	Outer width 485 mm	Ladder feet Ladder shoe	Depth of side-rails 74 mm	Width of side-rails 35 mm
Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 2 rungs	Step/Rung distance 273 mm	Max. load capacity 216 kg
Persons max. 2	Material Aluminium	Transport dimensions 750 x 488 x 85 mm, 2.5 kg	Business division MUNK Rettungstechnik	Order no. 116103

Facts

- Rescue ladder, made of aluminium, compliant with ÖNORM F4047
- Secure push-fit connections with spring-loaded locking pin
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance
- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes

- Upper ladder with box profile rung made of aluminium chequered plate
- Permissible load: 2 persons

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

