



Order no.: 063504

Safety barrier for emergency descent ladder

Type

Exit left

Exit right

Specification

Material
Galvanised steel

Transport dimensions 695 x 110 x 78 mm, 2.26 kg Business division MUNK Günzburger Steigtechnik Order no. 063504

Facts

- Automatic release mechanism for emergency ladder via safety barrier when the barrier is actuated
- Required for access points to ladder below a vertical height of 5.82 m and simultaneous use of emergency ladder, order no. 62446
- Galvanised steel barrier

Scope of supply

Safety barrier: 1 x

Installation material: 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria







