



Order no.: 063962

Rotating access protection unit

Specification

Material
Galvanised steel

Transport dimensions 700 x 665 x 510 mm, 14.5 kg

Transport dimensions 2 1250 x 130 x 75 mm, 4.5 kg Business division MUNK Günzburger Steigtechnik Order no. 063962

Facts

- The mechanical locking is opened by manually operating the toggle lever from above. Closing of the access guard and automatic locking is done manually from below
- Can be used with emergency ladder systems
- Can be mounted for opening to right and left, with integrated limit stop

Scope of supply

Access protection unit: 1 x

Installation material: 1 x

Assembly instructions: 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

Standards for quality and sustainability









