



Order no.: 033208

Double-sided rung ladder wood



Number of rungs

2x4

2x5

2x6

2x7

2x8

2x10

Specification

Working height 2.5 m	Step design Rungs	Number of steps/rungs 2x 4 rungs	Step/Rung distance 280 mm	Height 1.14 m
Ladder length 1.23 m	Base spread 830 mm	Lower outer width 500 mm	Upper outer width 380 mm	Depth of side-rails 60 mm
Max. load capacity 150 kg	Design type Freestanding Double-sided access	Weight 6.5 kg	Transport dimensions 1225 x 490 x 123 mm, 6.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 033208	Price € 119.00			

Facts

- Double-sided rung ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges

- Supplied as standard with practical bucket hook
- Spreader lock with two galvanized steel chains
- Rung distance: 280 mm
- Maximum load: 150 kg
- These products are covered by the statutory warranty


Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

