



Order no.: 071302

Rigid loading bridge LB 300

Type

LB 300

LB 400

LB 500

Specification

Length 2.6 m	Total length max. 2.92 m	Extendable No	Foldable No	Total width 1.05 m
Clear width 1 m	Bridgeable distance 2.4 m	Material Aluminium	Permissible total load 1000 kg	Surface Aluminium corrugated
Toe board height 63 mm	Mobile No	Wheelchair accessible Yes	Business division MUNK Rettungstechnik	Order no. 071302

Facts

- Loading bridge made of non-slip grooved aluminium
- For safe loading and unloading of vehicles and trailers
- With side toe boards
- For professional use

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

