



Order no.: 011013

## Rung window cleaner's ladder set with nivello® stabiliser



Number of rungs

### Specification

Working height <b>5 m</b>	Ladder length <b>4.69 m</b>	Step/Rung height <b>30 mm</b>	Step depth <b>30 mm</b>	Step/Rung distance <b>280 mm</b>
Upper outer width <b>128 mm</b>	Lower outer width <b>900 mm</b>	Stabiliser width <b>900 mm</b>	Inclination <b>70 °</b>	Depth of side-rails <b>73 mm</b>
Width of side-rails <b>25 mm</b>	Max. load capacity <b>120 kg</b>	Design type <b>To lean against   2-part</b>	Weight <b>12.7 kg</b>	Transport dimensions <b>1702 x 905 x 95 mm, 4.5 kg</b>
Transport dimensions 2 <b>2900 x 430 x 137 mm, 6.5 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>011013</b>	Price <b>€ 582.00</b>	

### Facts

- Rung window cleaner's ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged step-to-side-rail connection

- Secure push-fit connection with additional hook lock
- Upper ladder with castors and abrasion-resistant contact rubber pad with wedge cut-out
- Lower ladder with nivello® stabiliser for extra stability and safe ascent (enclosed separately)
- Rung distance: 280 mm
- Maximum load: 120 kg

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Industrial grade


Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

[Learn more](#)



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



### nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part




### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down




### Certificates

---



18KFP0030-02 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN 4567:1998  
DIN EN 131-  
3:2007  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAK-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK  
EK5/AK1 17-1:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

