



Order no.: 020608

3-section rung push-up extension ladder with nivello® stabiliser



Number of rungs

3x8	3x10	3x12	3x14
OAO	OXIO	OXIZ	OXII

Specification

Working height 6.9 m	Step design Rungs	Number of steps/rungs 3x 8 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Retracted length 2.5 m	Extended length 5.86 m	Outer width 500 mm	Stabiliser width 930 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Design type To lean against 3- part	Weight 17.2 kg	Transport dimensions 2482 x 495 x 205 mm, 17.2 kg
Business division MUNK Günzburger Steigtechnik	Order no. 020608	Price € 621.00		

Facts

- Rung push-up extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection



- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder from size 2x14 rungs with wall castors
- Corrosion-resistant guide fixtures
- Middle and upper ladders up to 3.0 m with nivello[®] ladder shoes
- Rung distance: 280 mm
- Ladder width: 500 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- RFACH
- The MUNK Group complies with a Code of Conduct



- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures







Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part





roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



The movable ladder shoe sets new standards in stability



Certificates





Corporate certifications

on sustainability criteria









