



Order no.: 041103

## Single-sided stepladder with castors



Number of steps

- 3**
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 12
- 14

### Specification

Working height <b>2.7 m</b>	Step design <b>Steps</b>	Number of steps/rungs <b>3 steps</b>	Platform included as step <b>Yes</b>	Step depth <b>80 mm</b>
Step/Rung distance <b>235 mm</b>	Type of non-slip protection <b>Aluminium corrugated</b>	Height <b>1.34 m</b>	Platform height <b>680 mm</b>	Base spread <b>700 mm</b>
Inclination <b>70 °</b>	Lower outer width <b>620 mm</b>	Depth of side-rails <b>73 mm</b>	Depth of side-rails, support <b>58 mm</b>	Width of side-rails <b>25 mm</b>
Castor diameter <b>80 mm</b>	Max. load capacity <b>150 kg</b>	Design type <b>Freestanding   Single-sided access   With castors</b>	Weight <b>8.7 kg</b>	Transport dimensions <b>1442 x 602 x 157 mm, 8.5 kg</b>
Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>041103</b>	Price <b>€ 445.00</b>		

### Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails

- 80 mm deep grooved steps and large platform
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- Four self-locking spring-loaded castors (Ø 80 mm)
- 'safe-cap' ladder joint
- Rigid connection through metal struts detachable on both sides
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Practical storage tray with integrated hooks and tool holders
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### **Scope of supply**

- Ladder: 1 x

### **Information on sustainability criteria**

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



The movable ladder shoe sets new standards in stability

[Learn more](#)




### Spring-loaded castors

- High stability, easy to change position
- Easy to move the ladder when it is set up
- Self-locking
- Also retrofittable and available as a spare part




### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




### Certificates



17KFP0689-04 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-  
3:2007  
EK5-AK1 17-  
02:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

