



Order no.: 065002

Socket

Material

Specification

Suitable for Shaft ladders

Transport dimensions 375 x 85 x 45 mm, 1 kg

Business division MUNK Günzburger Steigtechnik Order no. 065002

Facts

- Suitable for entry aid with order no. 65001
- Available in cured and passivated V4A (1.4571) stainless steel (round design) or galvanised steel (rectangular)
- Wall clearance 40 mm

Scope of supply

Push-fit section: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001



Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

Standards for quality and sustainability









