



Order no.: 115093

Multi-function ladder DIN
EN 1147

Specification

Rescue height 7.7 m	Working height min. 3.3 m	Working height max. 10.2 m	Intended use Rescue	Ladder length folded 2.3 m
Ladder length folded out without extension ladder 4.56 m	Ladder length folded out with extension ladder 5.56 m	Ladder length 2 multi- function ladders with plug-on ladder 9.2 m	Ladder length 2 multi- function ladders without plug-on ladder 8.2 m	Clear width as double ladder 1.6 m
Clear height of the attachment point 2.02 m	Setting angle 70 °	Clear width between rungs 250 mm	Clear width, upper ladder 370 mm	Clear width, lower ladder 370 mm
Outer width 570 mm	Ladder feet Ladder shoe	Depth of side-rails 85 mm	Width of side-rails 25 mm	Step/Rung height 28 mm
Step depth 29 mm	Number of steps/rungs 2x8 + 1x7 rungs	Step/Rung distance 280 mm	Max. load capacity 216 kg	Persons max. 2
Material Aluminium	Rung covering Standard (red)	Transport dimensions 195 x 570 x 2300 mm, 25 kg	Business division MUNK Rettungstechnik	Order no. 115093

Facts

- Aluminium multi-function ladder

- Rescue ladder compliant with DIN EN 1147
- Consisting of 3 ladder sections for universal applications
- With heat-insulating, non-slip plastic coating
- Secure push-fit connections with spring-loaded bolts on the hinge joint
- 4-fold edged rung-to-side-rail connection
- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- DIN mount for floodlights on the extension ladder
- Permissible load: 216 kg / 2 people

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability



TÜV NORD CERT
GmbH
Made in Germany



TÜVRheinland
ZERTIFIZIERT

Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Zertifiziert nach
DVS ZERT
EN 1090-1

Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022



Anteiliges Verzeichnis
AVPQ
Regulifizierter Unternehmen