



Order no.: 120200

Track carriage mobile container

Specification

Business division MUNK Rettungstechnik Order no. 120200

Facts

- Suitable for a variety of mobile containers from MUNK Rettungstechnik (track carriage attachment required)
- The rail running gear can be individually adjusted to the DB track gauge (1435 mm) and to the narrow gauge of the tramway (1000 mm)
- The rail trolley is only suitable for elevated tracks
- Produced using high-quality materials
- Withstands heavy loads
- Folding mechanism for transport position
- With parking brake (one wheel per axle)
- Wheel diameter 125 mm
- Track width adjustable: 1,000 mm (tram) and
- 1,435 mm (German Railways track width)
- Permissible load: 500 kg
- Scope of delivery: 2x rail system, 2x holder, 2x access ramp



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size

The materials used are listed in the technical specification

Resource-saving production: own photovoltaic systems

Energy-efficient consumption during production: LED lighting

Repairability, durability and quality: 15-year warranty on series products made in Germany

Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

Socially acceptable working conditions in production: fair wages, gender equality

Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

No health hazards for the users

More product pictures





Corporate certifications

Standards for quality and sustainability









