



Order no.: 120200

Track carriage mobile container

Specification

Weight
35 kg

Business division
MUNK
Rettungstechnik

Order no.
120200

Facts

- Suitable for a variety of mobile containers from MUNK Rettungstechnik (track carriage attachment required)
- The rail running gear can be individually adjusted to the DB track gauge (1435 mm) and to the narrow gauge of the tramway (1000 mm)
- The rail trolley is only suitable for elevated tracks
- Produced using high-quality materials
- Withstands heavy loads
- Folding mechanism for transport position
- With parking brake (one wheel per axle)
- Wheel diameter 125 mm
- Track width adjustable: 1,000 mm (tram) and 1,435 mm (German Railways track width)
- Permissible load: 500 kg
- Scope of delivery: 2x rail system, 2x holder, 2x access ramp

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

