

Order no.: 301303

# Tank truck ladder with rungs type 1



Design

Type 1

Type 2

Type 8



## Specification

Version Type 1	Total height max. 5.4 m	Total length max. 3.28 m	Total width max. 2.17 m	Platform height max. 4.3 m
Platform height min. 2.97 m	Platform length 1.08 m	Platform width 850 mm	Depth of side-rails 93 mm	Depth of side-rails, support 25 mm
Max. load capacity 150 kg	Swivel castors with locking device Ø 150 mm 4	Castors, Ø 280 mm 0	Transport dimensions 3280 x 2000 x 4300 mm, 391 kg	Business division MUNK Günzburger Steigtechnik
Order no. 301303				

## Facts

- 2-section tanker ladder made of aluminium with platform and protective cage (mandatory element, must be ordered separately)
- Protective cage in three variants can be ordered separately as mandatory equipment
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- Optional implementation with steps possible
- 4-fold edged rung-to-side-rail connection
- Guide and connecting parts in stainless steel
- Simple height adjustment from rung to rung thanks to cable winch and locking mechanism
- Platform with grating cover R13
- Railings with toe and knee boards on both sides
- Platform front side with 2-section safety door and protective basket (freely selectable, must be ordered separately)
- Undercarriages partly powder-coated in RAL 1021 and available in three designs
- Rung distance: 280 mm
- Delivery time: 15 days
- Note: The tanker ladder is constructed solely for access when performing operation or inspection tasks during loading or unloading of the tanker

### Scope of supply

- Ladder: 1 x
- Chassis: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



### Added value

---

#### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



#### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



# Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022