



Order no.: 020808

2-section rung push-up extension ladder with standard stabiliser



Number of rungs

2x8	2x9	2x10	2x11	2x12	2x13	2x14
2x15	2x16					
2x17	2x18					

Specification

Working height 5.2 m	Step design Sprossen	Number of steps/rungs 2x 8 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Retracted length 2.5 m	Extended length 4.08 m	Outer width 420 mm	Stabiliser width 930 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Design type Zum Anlehnen 2-teilig	Transport dimensions (plus packaging) 2481 x 425 x 147 mm, 11.2 kg	Business division MUNK Günzburger Steigtechnik
Order no. 020808				

Facts

- Rung push-up extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection

- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder from size 14 rungs with wall wheels
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct

- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Certificates



etestpk
25KFP0347-01 -
Test Certificate
"Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-
1.3:2021
PAK-
ANFORDERUNG
FÜR GS (PAH
REQUIREMENT
FOR GS) AFPS GS
2019:01 PAK

Corporate certifications

Standards for quality and sustainability

